









TRANSFORMER BOBBIN
INDUSTRIAL CO.,LTD.

Tel : 86-769-88789999 Fax : 86-769-88789989
http:// tbi-tw.com e-mail : tb6688@ms46.hinet.net

REVISIONS				
REV	SYM	DRAFTER	CHECKER	DATE
1		X.H.GU	G.F.YANG	05/26/15
2				
3				



NOTE:

- 耐壓4.0Kv /1.5mA 60S;
- 焊錫溫度:450°±10° 3SEC
- 任意一點強度須1.5kg MIN;
- 焊錫前拉力:1.0KG MIN,焊錫後拉力:1.5KG MIN;
- WINDING SPACE: 9.1mm*2.6mm=23.66mm²
- 與TBI-238-26211.11C(ATQ17-15A-CASE-B1-11)配套使用;

DWG NO.	ATQ17-15A-5P-TH-B1-11				
PART NO.	MATERIAL (BOBBIN)	MATERIAL (TERMINAL)	TERMINAL (PLATING)	PIN ALLOCATION	NOTE
TBI-238-26211.1106	PM-9630	CP WIRE	Sn	ALL PIN P/L=5.35±0.2	S
TBI-238-26211.1116	PM-9630	CP WIRE	Sn	ALL PIN P/L=4.5±0.2	H
TBI-238-26211.1126	PM-9630	CP WIRE	Sn	CUT PIN#3 P/L=5.35±0.2	
TBI-238-26211.1136	PM-9630	CP WIRE	Sn	CUT PIN#3 P/L=5.0±0.2	
TBI-238-26211.1146	PM-9630	CP WIRE	Sn	ALL PIN P/L=5.0±0.2	
TOLERANCE:0<L<=4:±0.1 4<L<=16:±0.2 16<L<=63:±0.3			UNIT : m / m		SCALE 1 : 1

Finish: 1. PB wire Immersion Sn on terminal : Thickness:Sn plating,100%,5 μ m (200 μ inches) min,Base nickel 0.625 μ m (25 μ inches) min.
2. CP wire Immersion Sn on terminal : Thickness:Sn plating,100%,5 μ m (200 μ inches) min.
3. Coplanarity deviation: 0.10 mm (0.004 inches) max.

REV 1